



SPECIFICATIONS

LIFTING CAPACITY	3,5t ≈ 7,700 lb
LIFTING HEIGHT	≤ 1900mm ≈ ≤ 74.80"
PLATFORM LENGTH	2,040mm ≈ 80.3"
PLATFORM WIDTH	610mm (each) ≈ 24" (each)
OVERALL WIDTH	2,160mm ≈ 85"
OVERALL HEIGHT (CLOSED)	115mm ≈ 4.53"
HYDRAULIC PRESSURE	25MPa ≈ 3,625psi
LIFTING TIME	< 60s
POWER SUPPLY	3.0kW ≈ 4hp
NET WEIGHT	750kg ≈ 1,650lb

Double Scissor Lift h1900 mm

Cod: 10002249

- Precision Leveling System**
Advanced design for fast and accurate adjustment
- Integrated Safety Solutions**
Dual hydraulic interlock system combined with hydraulic lock for maximum operator protection.
- Ultra-Low Profile**
Minimum height of just 115 mm, extending up to 1900 mm with optional adapters for different vehicle types.
- Extendable Platform**
Platform length of 1470 mm, extendable up to 2040 mm for larger vehicles.
- Versatile Installation**
The lift can be installed either above ground or flush-mounted (in-ground), offering maximum flexibility and optimal integration into the workspace.
- Robust Structure**
Solid steel scissor arms designed for strength and long-term reliability under demanding working conditions.
- Dual-Circuit Technology**
Ensures superior stability and operational safety during lifting and lowering phases.
- Standard supply**
The hoist is supplied with connecting pipework with a total length of 5 m. Please refer to the Manual for instructions on installing the control unit

Designed for quick tire service and light maintenance operations in professional body shops.

